

MEAT PROCESSING MACHINE

Food Smoke House

PRODUCT CODE	CATEGORY	ORIGIN
EQMH-CHINA-MY3172029	Meat Processing Machine	China, exported worldwide



Description

A microprocessor-controlled smokehouse supplied in four trolley sizes, from a single-trolley chamber at 25 to 38 kW up to a four-trolley chamber at 90 to 97 kW, all electrically heated. The controller operates the whole technological process in the chamber: the flaps, the smoke generator ignition, and the operating level the generator runs at. Programmable parameters include the temperature inside the product, the temperature inside the chamber and the chamber humidity, among others. Smoking is defined by holding those three against time, so programming them is what makes one batch repeat the last. The smoke generator burns chips of 3 to 10 mm with electric ignition. A built-in temperature sensor monitors combustion and automatically triggers the extinguishing system if the chips catch fire, which is the standard failure mode of a chip generator and the reason the sensor is fitted rather than optional.

Technical specification

TYPE Length: (mm) Width (mm) Height (mm) Weight (kg) Power (kW) I-trolley: 1260-1290 1450-1500 2565-2750 600-900 25~38 II-trolley: 2325-3390 1470-1700 2360-2750 750-1100 46~49 III-trolley: 3380-4590 1470-1700 2360-2750 900-1200 68~75 IV-trolley: 2365-5790 1470-3000 2360-2750 1000-1300 90~97

Request a quotation

Send your capacity, voltage and destination port and we will reply with drawings, a price and a lead time within one working day.

sales@equipmentsmachineschina.com



SCAN TO VIEW ONLINE