

STERILIZATION SYSTEM

Food Fully-automatic Tubular UHT Sterilizer

PRODUCT CODE	CATEGORY	ORIGIN
EQMH-CHINA-MY3172653	Sterilization System	China, exported worldwide



Description

Food Fully-automatic Tubular UHT Sterilizer

Technical specification

Production capacity (T/H) (options): 1 / 2 / 3 / 4 / 5 / 6 / 8 / 10 Heat exchanging area (ăži) (options): 20 / 28 / 35 / 45 / 52 / 60 / 75 / 88 Temperature of material inlet (?) (options): ?15 / ?15 / ?15 / ?15 / ?15 / ?15 / ?15 / ?15 Temperature of material outlet (?) (options): ?25 / ?25 / ?25 / ?25 / ?25 / ?25 / ?25 / ?25 Design temperature (?) (options): 150 / 150 / 150 / 150 / 150 / 150 / 150 / 150 Heat preservation time (?) (options): 5S / 5S / 5S / 5S / 5S / 5S / 5S / 5S Temperature of ice water inlet (?) (options): ?2? / ?2? / ?2? / ?2? / ?2? / ?2? / ?2? / ?2? Times of ice water (options): 3 / 3 / 3 / 3 / 3 / 3 / 3 / 3 Times of cooling water (options): 2 / 2 / 2 / 2 / 2 / 2 / 2 / 2 Times of hot water (options): 1.5 / 1.5 / 1.5 / 1.5 / 1.5 / 1.5 / 1.5 / 1.5 Pressure of steam inlet (Mpa) (options): ?0.5Mpa / ?0.5Mpa / ?0.5Mpa / ?0.5Mpa / ?0.5Mpa / ?0.5Mpa / ?0.5Mpa / ?0.5Mpa Maximum steam consumption (kg/h) (options): 200 / 250 / 330 / 410 / 480 / 550 / 650 / 780 Equipment weight (Kg) (options): 1600 / 2000 / 2400 / 2600 / 2800 / 3000 / 3800 / 4200

Request a quotation

Send your capacity, voltage and destination port and we will reply with drawings, a price and a lead time within one working day.

sales@equipmentsmachineschina.com



SCAN TO VIEW ONLINE