

## STRAPPING SEALING MACHINE

# Food Inkjet Batch Coding Machine

| PRODUCT CODE         | CATEGORY                  | ORIGIN                    |
|----------------------|---------------------------|---------------------------|
| EQMH-CHINA-MY3172778 | Strapping Sealing Machine | China, exported worldwide |



## Description

The Food Inkjet Batch Coding Machine is one of the Food Processing Equipment Line Machines Plants lines we manufacture and supply for export. This model is specified with a 180V supply and a machine weight of 1.2 Kg. Full technical detail is set out in the specification below. Listed under Strapping and Sealing Machine. It ships as a single unit or as part of a larger consignment, built to the destination's electrical specification and released with complete export documentation. Tell us the throughput you require and where it is going, and we will quote delivered with a lead time in writing.

## Technical specification

Printing speed: Max. 70 meters/min for 1 to 6 line printing at 300 dpi Printing area: 1 to 6 lines of 2000 characters from 1.2 to 12.7 mm high. Printing direction: Adjustable at any angle within 360 degree Print distance: Max. 6 mm from substrate down or in front. Prints using: Hewlett-Packard (hp) T1J 2.5 Print-head for spraying ink Printable images: Alphanumeric, Logo, Date/Time, Counter, Barcode, etc. UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, ENA128, PDF417, DATAMATRIX, QR Printing medium: Solvent/Oil based inks (black, white, red, blue, yellow, etc.) Inking medium: 42 cc disposable pre-mix ink in Cartridge form with head. Ink drying time: Min. 5 seconds on plastics & laminates. Impressions: Appx. 25 Lakh characters of 2 mm per

cartridge of ink. Message capacity: Store upto 999 messages with Message Name. Display: 4.3" full color Touch Screen LCD with LED backlight. Input device: 800 x 480 Touch Screen LCD, Pen Drive. Languages: English, Spanish, French, German, Chinese, etc. Power supply: 100-120 / 200-240 VAC at 50/60 Hz., 120 W Frequency: 50-60 Battery: 16.8V lithium battery, 10 hours use / 20 hours standby Operating range: 10 ~ +38°C 10% - 80% RH, non-condensing. Automation grade: Automatic Machine dimensions: H130 x W128 x D20 mm Weight: 1.2 kg excluding cartridge & battery. Weight Unpacked and dry: 39.68 lbs. (18 kg) Data Matrix: 0% to 90% RH non-condensing

### Request a quotation

Send your capacity, voltage and destination port and we will reply with drawings, a price and a lead time within one working day.

[sales@equipmentsmachineschina.com](mailto:sales@equipmentsmachineschina.com)



SCAN TO VIEW ONLINE