

GARAGE TYRE CARE EQUIPMENTS

Garage Automatic Tyre Changer

PRODUCT CODE	CATEGORY	ORIGIN
EQMH-CHINA-MY3059001	Garage Tyre Care Equipments	China, exported worldwide



Description

A garage automatic tyre changer removing and refitting tyres on wheel rims, with a powered bead breaker and mounting head so the work is done without levering by hand.

The specification that matters now is whether the machine handles low-profile and run-flat tyres, because those have stiff sidewalls that an older changer cannot seat without damaging the tyre or the rim, and alloy rims are easily marked. A leverless or assist-arm head addresses both. Rim diameter range should cover the largest wheels you see. Contact EMC Machines Manufactures with your rim size range and tyre types for a recommendation.

Technical specification

Heavy duty structure to guarantee proper working conditions at all times.

Metal side cover

Grease bucket support

TECHNICAL DATA:

Motor: Three phase: 230/400V 50hZ0, 75Kw

Chuck rotation speed (rev/min): 7.3

Max. torque to chuck (Nm): 1200

Self-centring lock: external: 10"-20"

Self-centring lock: internal: 12"-22.5"

Tool working span: 8"-24"

Max. tyre diameter (mm): 1050 MM (41")

Max. rim width (inches): 12"

Bead breaker cylinder power at 12 bar (kg): 3600kg (8000lbs)

Basic version weight (kg): 205

Request a quotation

Send your capacity, voltage and destination port and we will reply with drawings, a price and a lead time within one working day.

sales@equipmentsmachineschina.com



SCAN TO VIEW ONLINE