

Product Name :
Fish Feed Pellet Extruder

Product Code :
EQMH-CHINA-MY3006006



Description :

Fish Feed Pellet Extruder

Technical Specification :

Fish feed pellet extruder

The main extruder adopts frequency speed controlling with high automation and stable per-formation. The screws are made of the alloy steel and special craft, durable usage, high pressure, the screw life is longer. Adopting the building block structure and combining willingly according to the different demand.

The forced lubrication system, can guarantee the equipment transmission life longer.

Auto-temperature control system makes the temperature control more direct viewing and the parameter more precise.

Self-cleaning, when stopping, it can be cleaned with out disassembling.

Fish feed pellet extruder Operation steps:

Mix the raw materials and mix them.

Pour the mixed raw materials into the feed bin.

Turn on the cutter switch and adjust the cutter speed.

Adjust the distance between the cutter and the mold to control the size of the particles.

Turn on the host switch (green start button) to ensure the positive selection of the motor

Turn on the feeding switch and adjust the feeding speed. The final product pellets are obtained.

When the production is completed, turn off the main motor, turn off the cutter switch, and turn off the feed switch.

After stopping, remove the protective cover and keep the machine idling for one minute.

Take out the screw, clean it up, and clean up the mold for next use.



Equip Machines China

Email us at: sales@equipmentsmachines.com